EC-3, 07 FEB 2013 to 07 MAR 2013

1180 135.4 282.255 1180 180 **GND CON** 121.75 (Outbound) 1180 124.125 (TWR NORTH) 1180 226.675 O'HARE TOWERS 128.15 (Rwy 9L/27R) 120.75 126.9(CENTER) 273° 132.7 348.0 (CENTER) CHICAGO DEP CON SOUTH İ180 126.62 269.5 1180 1180 1180 1180 1180 TAKEOFF MINIMUMS: BRBIE Rwys 4L Standard with minimum climb of 547' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwys 4R: Standard with minimum climb of 690' per NM to 3000, then minimum climb of 350' per NM to 4000. Standard with minimum climb of 570' per NM to 3000, then Rwys 9L minimum climb of 350' per NM to 4000. Rwys 9R: Standard with minimum climb of 541' per NM to 3000, then **BACEN** minimum climb of 350' per NM to 4000. Rwys 10: Standard with minimum climb of 672' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwys 14L: Standard with minimum climb of 547' per NM to 3000, then minimum climb of 350' per NM to 4000. **BLOKR** Rwys 14R: Standard with minimum climb of 670' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwys 22L: Standard with minimum climb of 807' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwys 22R: Standard with minimum climb of 521' per NM to 3000, then minimum climb of 350' per NM to 4000. Standard with minimum climb of 532' per NM to 3000, then

NOTE: TURBOJET departures maintain 250 KIAS until advised by ATC. NOTE: If unable to accept climb gradient, advise ATC as soon as

possible prior to departure. NOTE: DME/DME/IRU or GPS Required.

NOTE: RNAV 1

Rwy 28:

Rwy 32L:

NOTE: RADAR Required.

NOTE: ROBERTS TRANSITION: For aircraft inbound to CMI or STL, or

minimum climb of 350' per NM to 4000. Rwy 27R: Standard with minimum climb of 631' per NM to 3000, then minimum climb of 350' per NM to 4000.

minimum climb of 350' per NM to 4000.

minimum climb of 350' per NM to 4000. Rwys 32R: Standard with minimum climb of 587' per NM to 3000, then minimum climb of 350' per NM to 4000.

Standard with minimum climb of 685' per NM to 3000, then

Standard with minimum climb of 631' per NM to 3000, then

as assigned by ATC.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale. CHICAGO, ILLINOIS

ROBERTS

RBS

BEKKI